

R Series



R215



R15M



R115



R12M



R112



R118W

Delivering Yamaha Quality and Outstanding Cost Performance.

Yamaha's Club Series loudspeakers have long been a popular choice among audio professionals and musicians for offering quality components, excellent performance, and durability at an affordable price. In that same tradition, the R-Series offers powerful sound, practical function, features, and audio quality at a price that is even harder to beat.

Features like high-power woofers, titanium high frequency compression drivers, and constant directivity horns, deliver audio performance that is hard to obtain in this price range. Neutrik's Speakon connectors, durable MDF enclosures, big heavy-duty steel handles, durable finishes, and heavy-duty grills offer convenience and protection that professionals look for in a sound system.

Enclosures are designed with rounded fronts that look better when multiple units are arranged in an array and the series offers six different models, designed to meet the needs of a variety of budgets and applications.

**Some models may not be available in all areas.*

R Series

GENERAL SPECIFICATIONS

| Model | R215 | R115 | R112 | R15M | R12M | R118W | |
|-------------------------|---|--|--|--|---|--|----------|
| Type | | | 2-way bass reflex | | | bass reflex | |
| Frequency range (-10dB) | 40Hz-20kHz | 50Hz-20kHz | 55Hz-20kHz | 50Hz-20kHz | 55Hz-20kHz | 35Hz-3kHz | |
| Nominal coverage | | 90H x 40V | | 40H x 90V | | - | |
| Nominal Impedance | 4Ω | 8Ω | 8Ω | 8Ω | 8Ω | 8Ω | |
| Power rating | PGM | 1000W | 500W | 400W | 500W | 400W | 500W |
| | MAX | 2000W | 1000W | 800W | 800W | 800W | 1000W |
| Sensitivity (1W, 1m) | 98 dB SPL | 98dB SPL | 97dB SPL | 98dB | 97dB | 97dB | |
| Component | LF | 15" cone X 2 | 15" cone | 12" cone | 15" cone | 12" cone | 18" cone |
| | HF | 1.75", Ti vc, CD-Horn | 1.75", Ti vc, CD-Horn | 1.75", Ti vc, CD-Horn | 1.75", Ti vc, CD-Horn | 1.75", Ti vc, CD-Horn | - |
| Connectors | Speakon x 1, Phone x 2 | Speakon x 1, Phone x 2 | Speakon x 1, Phone x 2 | Speakon x 1, Phone x 2 | Speakon x 1, Phone x 2 | Speakon x 1, Phone x 2 | |
| Rigging points | n/a | M10 x 3 | M10 x 3 | n/a | n/a | n/a | |
| Pole mount socket | n/a | 35 mm | 35 mm | n/a | n/a | n/a | |
| Dimension (W x H x D) | 520 x 1175 x 600 (20-1/2" x 46-1/4" x 23-5/8") | 520 x 765 x 470 (20-1/2" x 30-1/8" x 18-1/2") | 480 x 695 x 400 (18-7/8" x 27-3/8" x 15-3/4") | 745 x 490 x 400 (29-5/16" x 19-5/16" x 15-3/4") | 675 x 450 x 380 (26-9/16" x 17-11/16" x 14-15/16") | 562 x 811 x 639 (22-1/8" x 31-15/16" x 25-1/8") | |
| Weight | 69.0 kg (152.12 lbs.) | 35.0 kg (77.16 lbs.) | 26.5 kg (57.32 lbs.) | 30.5 kg (67.24 lbs.) | 24.0 kg (52.91 lbs.) | 49.5 kg (109.13 lbs.) | |

DIMENSIONS

unit : mm

